




PROFILE MIKE 7661



PROFILE MIKE

■ painted aluminum, plastic

■ 7661




● 1xGU10 R50, max 15W only LED



PROFILE ZOOM LED 7625



PROFILE INDIA 7657




PROFILE INDIA

■ painted aluminum, plastic

■ 7657



● 1xGU10 R50, max 15W only LED



PROFILE ZOOM LED

■ painted aluminum, plastic

■ 7623 3000K ■ 7624 4000K

■ 7625 3000K ■ 7626 4000K



BEAM CONE


BEAM ANGLE
15°



BEAM ANGLE
50°



PROFILE FOCUS 7621



PROFILE FOCUS LED

■ painted aluminum, plastic

■ 7618 3000K ■ 7620 4000K

■ 7621 3000K ■ 7622 4000K



Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection
7618	10W LED	3000K	600 lm	36°	>90	~220-230 V, 50/60 Hz	■	>0.9	IP20
7620	10W LED	4000K	600 lm	36°	>90	~220-230 V, 50/60 Hz	■	>0.9	IP20
7621	10W LED	3000K	600 lm	36°	>90	~220-230 V, 50/60 Hz	■	>0.9	IP20
7622	10W LED	4000K	600 lm	36°	>90	~220-230 V, 50/60 Hz	■	>0.9	IP20
7623	9W LED	3000K	600 lm	15-50°	>90	~220-230 V, 50/60 Hz	■	>0.9	IP20
7624	9W LED	4000K	660 lm	15-50°	>90	~220-230 V, 50/60 Hz	■	>0.9	IP20
7625	9W LED	3000K	600 lm	15-50°	>90	~220-230 V, 50/60 Hz	■	>0.9	IP20
7626	9W LED	4000K	660 lm	15-50°	>90	~220-230 V, 50/60 Hz	■	>0.9	IP20