



max 410 kg

4 cm

7 cm

PICCO LED S 9106

PICCO LED S

aluminum

9106

cut out ø 38 mm



max 620 kg

6 cm

9 cm

PICCO LED M 9105

PICCO LED M

aluminum

9105

cut out ø 55 mm



max 780 kg

7.5 cm

9.5 cm

PICCO LED L 9104

PICCO LED L

aluminum

9104

cut out ø 65 mm



max 500 kg

11 cm

14 cm

PAOLI 9554

PAOLI

steel, glass

9554

1xGU10 R50, max 10W only LED

cut out ø 100 mm

IP67



max 500 kg

6.7 cm

11.7 cm

PAOLI 9554

PAOLI


steel, glass

9554

1xGU10 R50, max 10W only LED

cut out ø 100 mm

IP67



max 500 kg

6.2 cm

6 cm

7.2 cm

PAT LED 8162

PAT LED

painted aluminum, plastic PC

8162

cut out ø 56 mm



max 500 kg

6.5 cm

6 cm

6.3 cm

CIRCLET LED 8163

CIRCLET LED

painted aluminum, plastic PC

8163

cut out ø 57 mm

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
9106	2W LED	3000K	60 lm	25 °	≥ 80	~220-230 V, 50/60 Hz	⊕	>0.5	IP67	10000h
9105	2W LED	3000K	80 lm	25 °	≥ 80	~220-230 V, 50/60 Hz	⊕	>0.5	IP67	10000h
9104	3W LED	3000K	200 lm	25 °	≥ 80	~220-230 V, 50/60 Hz	⊕	>0.5	IP67	10000h

Item No.	Power	Colour temp.	Luminous flux	Beam angle	Colour Rendering Index (CRI)	Input	Safety type	Power factor	Ingress protection	Lifetime
4454	2W LED	3000K	100 lm	30 °	≥ 80	~220-230 V, 50/60 Hz	⊕	>0.5	IP67	10000h
8162	3W LED	3000K	12 lm	25 °	≥80	~220-230 V, 50/60 Hz	⊕	>0.5	IP65	10000h
8163	3W LED	3000K	120 lm	50 °	≥80	~220-230 V, 50/60 Hz	⊕	>0.5	IP65	10000h

SILVER

BLACK

SILVER

BLACK

OUTDOOR LIGHTING

Nowodvorski
LIGHTING

568

569